

## K10H-6060

伸臂架式机头360度旋转智能模板机带升降功能  
360° DEGREE MACHINE HEAD ROTATE  
AND LIFTING AUTOMATIC TEMPLATE MACHINE



### 产品简介 Product introduction

360度旋转机头缝制，实现任意角度完美线迹。  
Rotate 360° machine head sewing, achieve perfect stitch at any Angle

### 性能参数 The performance parameters

有效缝纫范围 Sewing range	X轴60×Y轴60cm X: 60cm Y: 60cm	操作显示屏 Operating display	全液晶：触摸式液晶显示屏 Full liquid crystal touch liquid crystal display screen
最高缝速 Speed	200rpm-3500rpm (需看机型、针距、材料、缝线情况) 200rpm-3500rpm(depend on the machine model/needle distance, material, thread)	传动结构 Transmission structure	齿带导轨模组 Toothed belt guide module
剪线机构 Trimming mechanism	圆刀剪线机构，适用性更广泛 Circular cutter wire cutting mechanism, more extensive adaptability	特殊功能 Special function	机头360度旋转，带机头升降功能 Outstretched arm machine head 360° sewing Machine head lift function
针距 Stitch length	0.5mm 至 6mm 0.5mm to 6mm	程序记忆载体 Program memory carrier	EPROM内存 EPROM memory
可识别模板文件 Identify template files	电子标签射频识别：识别数量无限 RFID: the identification number is unlimited	缝纫机马达 Sewing motor	650W直接驱动伺服马达 650W Direct drive servomotor
缝针 Needle number	DP×5(#7-#24); DP×17 (#11-#24)	电源规格 Power specification	220V 600W
程序输入装置 Program input device	电脑USB数据线或U盘 Computer USB cable or USB drive	使用空气规格 Air pressure specifications	0.25-0.4MPa(最大0.5MPa) 0.25-0.4MPa (max 0.5MPa)